

## Large Closed body truck

Drivetrain: 4X2  
Drive type: Right Hand Drive  
Driver cabin: Day and night cab/large cab  
Engine power: Minimum Peak power 130 kW  
Engine torque: Minimum Peak torque 675 Nm  
Fuel: Diesel  
Permissible total weight 13500 KGS  
Permissible axle load, axle 1 4700 KGS  
Permissible axle load, axle 2 9300 KGS  
Gearshift: Manual transmission  
Steering: Power steering  
Exhaust brake, with constantly open throttle valve  
Engine, start/stop system  
refitting: Fuel pre-filter, water separator  
Front springs, parabolic  
Rear spring, parabolic  
Stabilizer front axle  
Stabilizer, rear axle, under frame  
Spare wheel carrier, under body; full size spare tyre

Main tank, 200 liters, Tank-cap lock  
Dual-circuit full air brakes  
Load sensing brake system  
Automatic brake adjusting  
Anti-lock braking system (ABS)  
Compressed-air drier (single-chamber system)  
Brake connection, 2-line, behind cab  
Hydraulic cab tilting mechanism  
Cab rear wall without window  
Roof hatch/vent, roof  
Cab steps, movable  
Side Mirrors, electrically adjustable  
Wide-angle exterior mirror on front passenger side  
Ramp/ kerb observation mirror on co-driver's side  
Electrically adjustable rear-view mirror,  
Wide angle mirror on driver's side, heated  
Sun visor, exterior, transparent  
Additional keys or remote-control transmitter

Driver's standard suspension seat,  
Co-driver's seat, static,  
Steering column bracket adjustable  
multi-function steering wheel  
Inst. cluster, graphics-capable display, eco-meter  
Speedometer, km, Outside temperature gauge  
Reversing warning device  
Driver Information System  
1 or 2 DIN radio, 2 speakers with AUX, CD, USB, Antenna + kit  
Air conditioning system

Stowage facility above windscreen, 2 compartments

Trailer socket, 15-pin

Headlamp range adjuster

Headlamp unit, H7, with clear lens look

Protective grilles, headlamps

6-part tail light cluster with reflector

Side marker lights

First aid kit, Fire extinguisher, Hazard warning triangle, Jack

Labels/publications, English

### **Cargo Body**

Closed body, rigid and waterproof construction

Plywood body: 20 mm

Floor: 24 mm carply floor with anti-slip, metallic floor beneath the carply floor for additional strength

Length inside: 5.700 mm

Width outside: 2.500 mm

Height inside: ca 2.500 mm

Inside: 2 units of LED-lights

2 rear doors

Hydraulic Tail Liftgate

Capacity 1.500 kg, 24 V

Preferred Makes: Mercedes, Isuzu or Mitsubishi which have spare parts and service centers throughout Kenya