

PR9209727 20-Seater Bus

SPECIFICATIONS:

RIGHT HAND DRIVE

Turbo Charged Intercooled Engine 3783cc, 5F+1R , power steering, Dual circuit full air S-cam brakes.

Mild steel superstructure. Floor structure made of 100 x 50 x 3 R.H.S. M12 bolts used to secure the same to the chassis. Sides made of 40 x 40 x 3.0mm R.H.S network and roof of 40 x 40 x 2.0mm

R.H.S network. The super structure to be dipped in red oxide enamel & fitted with Anti-rust bars

2. Exterior paneling will be 20g galvanized and the rest will be mild steel
3. Original cabin cowl will be maintained to determine front shape
4. Single piece curved front windscreen & single piece emergency glass at rear fitted with weather strip.
5. Manually operated passenger door situated behind the front axle for entry and exit, inward opening.
6. Fixed high back seats with split backrest and single bench. 7. 2 X 2 seating arrangement
8. Seats to be covered with Grey Rexene / Auto fabric
9. Seats to be fitted with 2-point manual seat belts, except for exposed seats to be fitted with 3-point retractable seat belts
10. Floor to be of M/S plate & covered with dotted grey PVC Vinyl flooring to finish
11. Aisle and step wells to be lined with aluminum chequered plate
12. Roof to be covered with Grey Formica to finish. All joints to be covered with aluminum moldings to finish
13. Roof coves, window pillars and side walls to be covered with carpet to finish

14. 3pcs interior bulb type lights for passenger area and 1pc bulb type light for driver area.

15. Interior parcel shelves to be fabricated out of M/S pipes and painted to finish

16. Window glasses will all be clear and local. Top glasses will be fixed and bonded whereas bottom glasses will be sliding in an aluminum frame or vice versa

17. No undercarriage compartments & no exterior roof rack

18. Exterior paint to be one Acrylic colour.

19. One Year Warranty